



Material Engineering Asia Pacific Limited, company of I.H.G Fin Group  
 Unit 2702, 27/F, The Centrium, 60 Wyndham Street, Central, Hong Kong  
 +852 58044402 - +86 13758248140  
 www.mysunwind.com  
 info@materialengineeringasiapacific.com  
 sean@ihgfin.com

Model		SPG6500	SPG6500E2
Generator	AC Frequency	50Hz	50Hz
	Rated AC Voltage	220V/230V/240V	
	Surge AC Output	5500W	5500W
	Rated AC Output	5000W	5000W
	Power factor COSΦ	1	
Engine	Phase	Single phase	
	Engine Type	OHV, Air cooled engine	
	Displacement	389cc	
	Maximum Power Output	13HP	
	Ignition System	T.C.I.	
	Starting System	Recoil	Electric & Recoil
	Fuel	Unleaded Gasoline	
	Fuel Tank Capacity	25 L	25 L
	Run Time(appr.) on One Tankful @3/4 Load	10 h	10 h
	Noise Level @ 7 m	72dB(A)	72dB(A)
Gen set	Carton Dimensions (L x W x H)	700 x 525 x 560 mm	815x 560 x 575 mm
	Net/Gross Weight(appr.)	80.3 kg/84.3kg	92kg/95kg(with battery15AH)
Configuration	Electric Starting System		●
	Automatic Voltage Regulator	●	●
	Fuel Meter	●	●
	Oil Warning System	▲	▲
	Voltmeter	●	●
	12VDC Output	▲	▲
	DC Charging Cord	▲	▲
	AC Circuit Breaker	●	●
	2-wheel transport kit		●(10" wheels)
	Automatic Decompression System	●	●
Brushless Alternator			
Brush Alternator	●	●	

